

	Α			В		Α			В			A		В			Α			В
	Feet	Inch	Feet	Inch		Feet I	nch	Feet	Inch	_	Feet	Inch	Feet	Inch	_	Fe	et	Inch	Feet	Inc
1	┞			Щ	24	╙		_	Ш	47	\perp	_	_	Ш		70				L
2	_	_			25	┞		<u> </u>	Щ	48	-	╀	┞	Ш	-	71				L
3	_	_		Щ	26	\vdash		<u> </u>	Ш	49	\perp	\bot	₩	Ш	7	72				L
4					27	lacksquare			Ш	50	\perp	_	_	Ш	7	73				L
5				Ш	28	\perp			Ш	51				Ш	7	74				L
6				Щ	29	$oxed{oxed}$			Ш	52	\perp		_	Ш	7	75				L
7					30				Щ	53		_	\perp		7	76				L
8				Щ	31				Ш	54			_	Ш	7	77				L
9					32				Ш	55		\perp			7	78				
10					33				Ш	56					7	79				L
11					34					57					8	30				
12					35					58					8	31				
13					36					59					8	32				Ĺ
14					37					60					8	33				Ĺ
15					38					61					8	34				
16					39					62					8	35				Г
17					40					63					8	36				
18					41					64					8	37				Г
19	2 2				42					65					8	38				
20					43					66		1			8	39	12			
21					44				П	67					9	90				Г
22		П			45			П	П	68		1			9	91				
23					46			П		69					9	92				Г
des	on Po		B		ease prov	ride de	escrip	tions:	Handr	ails - Slid	Α	aterfall	В		k · Planto	ers, et	tc.			
Enc	at IIIG	1	IIICI							h	- T		1							_
Fee	$\neg \neg$			+					-	 	\dashv	+	+	+						
Fee	\top	+							- 1	<u>'</u>				_						_
Fee	+	#	-	+-						1: 1				- 1						
Fee	+	+		+						j	\dashv	+	+	+						
Fee		+								j k	1		+	+						
Fee										1										
Fee										l m										
Fee										1										
	TANT!	The	dista	ance fro	om "A" t	o "B"	is _		ft.	l m	in.									
PORT										l m n		leck?			Yes 🗀			ft		n.
PORT										l m n		deck?	ut-out	,	Yes Yes Yes	No 🗆		ft		n.

Job Name ______ Of _____



Job Name	Page	0f	
----------	------	----	--

1. Establish two points, "A" & "B", ("A" must be to the left of "B" facing the pool) on the deck area about 2/3 the length of the pool; 20'-25' is typical. (The longer the line, and the farther away from the pool, the better for accuracy).

Mark your "A-B" points with stakes in the ground or chalk marks on the deck. Show "A-B" line on diagram along with distance from "A-B" and the direction of your points around the pool

IMPORTANT: The "A-B" line, or extensions of, CANNOT intersect or come with 3' of pool.

2. Using chalk marks. Number points in a clockwise direction along the inside edge of the pool at approximately 2'-3' intervals. The tighter the radii, provide more points, every 1'-2'. Straight lines or broad radii less points, every 3'-4'. The more points the better. Be careful and number all corners, changes of direction and obstacles. You must provide "A-B" points for all corner points.

Use letters A, B, C to mark obstacles such as ladders, handrails, grab rails, slide legs, dive stands, rocks, spillways, spa walls, fill spouts, etc.

- 3. Measurements are now taken from "A" to point #1, then point #2, and all around the pool, fill in the chart. Than measure from "B" to the same point #1, then #2, and all around the pool as for "A". List the measurements in column format as in the sample form. Measure the length and width of the waterline using two established numbered points on pool
- 4. Use a sketch to indicate inside pool dimensions, Show all obstructions on deck, (slides, grab rails, etc.) planters and how far back they are from pool edge, rocks, spas, waterfalls, etc. Please mark by letters A, B, C anything measured that is not at the water's edge.
- 5. For obstructions that are flush with the pool wall, provide "A-B" points and tell us where the raised or rock area begins and ends.
- 6. Show us on the diagram where there is less than 3' of deck.
- Remember; don't show removable obstructions when possible.
- A photo is required for all pools with unusual obstacles.

HINTS: Only through accuracy can we ensure a proper fit. We make the cover from your dimensions; spend the time and be as accurate as possible.

WARNING! The use of stakes and tubes on over 30% of cover, does not meet ASTM standards for safety covers.

